


Emergency Stop

- Plug & play E-stop switch.
- Multi-voltage.
- TE DEUTSCH connector on fly lead.
- Incorporated strain relief on both ends of lead.
- Resistant to shock, vibration, dust and moisture
- Environmentally sealed IP67, IP6K9K, when installed to manufacturer's specifications.
- Optional recessed mounting panels with E-Stop legend.

Voltage: 9-32V Max Current Rating: 10A Continuous Terminals: Copper Zinc Alloy Contacts: Silver Alloy Switch: Polyamide Connector: Thermoplastic Cable Length: 180mm Thread Size: M30 x 1.5 Vibration: ISO 16750-3 Ingress Protection: IP67, IP6K9K Operating Temperature : -40°C to 85°C







KISSLING - 90°

Part No. Description

TMS47 Single Pole. 1 x N/O, 1 x N/C

Button Type

Latching (Turn to Release)

Kit Contains:

- 1 x KISSLING E-Stop with integrated TE DEUTSCH connector
- 1 x Mating Connector components, including Housing, Wedgelock & size 16 Green Band Contacts to suit.







KISSLING - Accessories

Part No. Description

TMS54 Recessed panel mounting bracket – Nylon

TMS56 Recessed panel mounting bracket – Steel, rubber gasket and round legend

TMS55 Round legend – "EMERGENCY STOP" – Yellow



